



Technical information

- AKVA PRO 750-T9300750
- Max pressure 6 bar
- Max temperature 60 °C
- Material Stainless steel[304]
- Insulation - Closed cell polyurethane
- Insulation thickness 100 mm
- Thermal losses 94W
- Energy class N/A
- Drain connection: DN25(1")
- Venting connection: DN25(1")
- Planned manufacturing series: 1 pcs
- Baffle plates - pc[s]:

Handling

- Cross measure: 2153 mm
- Weight (empty): 180 kg

Additional requirements

Components:

- C1 DN65-PN16-ZN Flange
- C2 DN65-PN16-ZN Flange
- C3 DN15-80-Socket SS
- C4 DN15-80-Socket SS
- C5 DN15-80-Socket SS

Surface finish and packing:

Main surface:
Painted sheet metal
Color: White

End cover
ABS plastic cover
Color: Red

Packing:
Normal packing

KyIRST750

KyIRST750

This pressure vessel is designed and manufactured in accordance with the sound engineering practice of a Member State in order to ensure safe use. Welded joints are inspected in accordance to EN 5817 – Class C.

Drawn	2023-03-14	ENo
AKVATERM		
Kaarielankatu 21, 67100 Kokkola, Finland www.akvaterm.fi		



Metro Therm Ab
RST750001-2