



**Technical information**

- AKVA PRO 4000-T9104000
- Max pressure 3 bar
- Max temperature °C
- Material Carbon steel
- Insulation - Closed cell polyurethane
- Insulation thickness 100 mm
- Thermal losses 236W
- Energy class N/A
- Drain connection: DN25(1")
- Venting connection: DN25(1")
- Planned manufacturing series: 1 pcs
- Baffle plates - pc[s]:

**Handling**

- Cross measure: 2710 mm
- Weight (empty): 530 kg

**Additional requirements**

**Components:**

- C1 DN50 ST Socket -Normal
- C2 DN50 ST Socket -Normal
- C3 DN50 ST Socket -Normal
- C4 DN50 ST Socket -Normal
- C5 DN15 ST Socket -Normal
- C6 DN15 ST Socket -Normal
- C7 DN15 ST Socket -Normal
- C8 DN50 -Long [Parallel]
- C9 DN50 -Long [Parallel]
- C10 DN50 -Long [Parallel]
- HE1 LK S NS200
- HE2 NS200 Hatch

**Surface finish and packing:**

Main surface:  
Painted sheet metal  
Color: White

End cover  
ABS plastic cover  
Color: Red

Packing:  
Normal packing

This pressure vessel is designed and manufactured in accordance with the sound engineering practice of a Member State in order to ensure safe use. Welded joints are inspected in accordance to EN 5817 – Class C.

Drawn	2021-05-20	JMa
<b>AKVATERM</b>		
<small>Kaarlielankatu 21, 67100 Kokkola, Finland www.akvaterm.fi</small>		



**AKVA 4000 EK**  
**5235102001-2**