



Technical information

- AKVA PRO 750-T9100750
- Max pressure 3 bar
- Max temperature °C
- Material Carbon steel
- Insulation - Closed cell polyurethane
- Insulation thickness 100 mm
- Thermal losses 94W
- Energy class N/A
- Drain connection: DN25(1")
- Venting connection: DN25(1")
- Planned manufacturing series: 1 pcs
- Baffle plates - pc[s]:

Handling

- Cross measure: 2153 mm
- Weight (empty): 190 kg

Additional requirements

Components:

- C1 DN50 ST Socket -Normal
- C2 DN50 ST Socket -Normal
- C3 DN50 ST Socket -Normal
- C4 DN50 ST Socket -Normal
- C5 DN15 ST Socket -Normal
- C6 DN15 ST Socket -Normal
- C7 DN15 ST Socket -Normal
- C8 DN50 -Long [Parallel]
- C9 DN50 -Long [Parallel]
- C10 DN50 -Long [Parallel]
- HE1 NS200 Hatch
- HE2 NS200 Hatch

Surface finish and packing:

Main surface:
Painted sheet metal
Color: White

End cover
ABS plastic cover
Color: Red

Packing:
Normal packing

Drawn 2021-11-08 JMa



AKVA 750 E
5235056003-2