



**Technical information**

- AKVA PRO 500-T9200500
- Max pressure 10 bar
- Material Ferritic stainless steel
- Insulation - Closed cell polyurethane
- Insulation thickness 100 mm
- Thermal losses 74W
- Energy class B
- Drain connection: DN25(1")
- Venting connection: DN25(1")
- Planned manufacturing series: 1 pcs
- Baffle plates - pc[s]:

**Handling**

- Cross measure: 1850 mm
- Weight (empty): 110 kg

**Additional requirements**

**Components:**

- C1 DN50-80-Socket SS
- C2 DN50-80-Socket SS
- C3 DN50-80-Socket SS
- C4 DN15-80-Socket SS
- C5 DN15-80-Socket SS
- C6 DN20-80-Socket SS
- C7 DN15-80-Socket SS
- C8 DN50 -SS Long socket [Parallel]
- C9 DN50 -SS Long socket [Parallel]
- C10 DN50 -SS Long socket [Paral]

**Surface finish and packing:**

Main surface:  
Painted sheet metal  
Color: White

End cover  
ABS plastic cover  
Color: Red

Packing:  
Normal packing

VF-500

This pressure vessel is designed and manufactured in accordance with the sound engineering practice of a Member State in order to ensure safe use. Welded joints are inspected in accordance to EN 5817 – Class C.

Drawn	2019-10-01	ENo
<b>AKVATERM</b>		
Kaarielankatu 21, 67100 Kokkola, Finland www.akvaterm.fi		



**Metro Therm Ab**  
**VF-500001-2**